

Official Offer Sheet

Bus Model:	JS6128GHBEV	Offer date:	2024-09-19
			For standard configuration

Dimensions (mm)	12000×2550×3230	Curb weight (Kg)	12000
F/R overhang (mm)	2650/3200	Max G. V. W (Kg)	18000
Wheel base (mm)	6150	Seat capacity/ Standing passengers	35+1/83
Approach/departure angle (°)	7/7	Max speed (km/h)	69

System	Item	Standard	Optional
Power system	Electric motor	DANA MD130	
	Driving form	Direct-driven	
High-pressure system	High voltage electronic control system	Four in one system	
	Charging system	Plug-in charging port, GB/T20234.3-2015n	
	Power battery	CATL 303.4Kwh(CATL) (10 packs)	
Body structure	Floor	Two steps	
Driving system	Suspension	Air suspension (air bag: front 2 middle 4 rear 4), with front&rear stabilizer bar	
	Front axle	HANDE front disc axle, load capacity 7.5T	
	Rear axle	HANDE rear drum axle, load capacity 13T	
	Tire	275/70R22.5 tubeless radial tire without spare tire	
	Rim	Steel rim	
Control system	Steering gear	Chinese integral power steering (LHD)	
	Steering wheel	Four-way adjustable, ordinary steering wheel	
	Body lift	NO	
Braking system	ABS	Chinese ABS	
	Brake	Pneumatic double circuit air front disc & rear drum brake, equipped auto slack adjuster on rear drum brake (auto slack adjuster along with the front disc brake) ; Parking brake	
	Retarder	Electric motor with retarder function (No additional retarder)	
	Air cylinder	Steel air storage cylinder, automatic water discharge valve	
Power train system	Gearbox	NO	
	Clutch	NO	
Cooling system	Battery liquid cooling	NO	

	Cooling system	ATS cooling fan	
Security system	Interior fire extinguisher	Two 4kg dry powder manual fire extinguishers	
	Cabin fire extinguisher	Automatic fire extinguisher for motor compartment and battery compartment	
	Cabin temperature alarm system	NO	
Security system	LDWS	NO	
	AEBS	NO	
	Emergency hammer	Emergency hammer	
Interior	Air duct	Standard air duct	
	Dashboard	Standard dashboard	
	Interior materials	Punch aluminum plastic composite board	
	Wall materials	PVC board	
	Handrail & guardrail	Spraying plastic handrail, guardrail, protection board behind the rear passenger door	
	Hand ring	NO	
	Driver surround	Luxurious driver whole-surround	
	Floor leather	Wear-resistant floor leather	
	Floor	Bamboo floor	
	Front sunshade	Manual sunshade for the front shield	
	Side sunshade	Side rolling curtain for driver window	
	Curtain	NO	
Exterior	Passenger door	Front and middle double pneumatic swinging door	
	Emergency	NO	
	Side window	Built-in adhesive sliding window, double-layer glass for the whole bus	
	Window color	F green	
	Front windshield	Double laminated glass	
	Tire trim cover	NO	
Seats	Driver seat	Shock absorber adjustable driver' s seat, with self-retractable 3-point seatbelt	
	Passenger seat	Special bus seats for new energy vehicles	
Cabin	Luggage compartment	NO	
	Partition wall	NO	
Rearview system	rearview mirror	Pole type rearview mirror (Short left and long right)	
	Interior mirror	YES	
	Reverse monitor	NO	
Air conditioner	A/C	Roof mounted single cold electric A/C (maximum cooling capacity: 18-37KW)	
	Driver' s fan	YES	
	Sunroof	One emergency exit	
Electric system	CAN bus	CAN instrument	
	Driving recorder	NO	
	Battery	Standard battery	
	Lighting	Peripheral lamps, inner ceiling light, step light	
	Guideboard	Front, rear Guideboard (LED)	

Strategic Sustainable Development Limited. (SSD)
 DK264, Aggrey Road, GT-093-0374
 Tema Community 2,
 Great Accra, Ghana



"downwards never upwards forever"

	Inside scroll display	NO	
	Windshield wipers	Standard wipers	
	Horn	Standard horn	
	USB Charging port	1 USB charging port for the driver	
	Electronic clock	NO	
	Lighter	NO	
Multi-media	Audio-visual system	Radio with MP3 function	
	Advertising display	NO	
Service facility	Tow hook	Front tow hook	
Tools	Tools	Tools and 2 parking wedges	
Others	Use conditions	City road, city bus	

Pictures for reference:



Strategic Sustainable Development Limited. (SSD)
DK264, Aggrey Road, GT-093-0374
Tema Community 2,
Great Accra, Ghana



"downwards never upwards forever"

